



300 V Power 5W-40

Oil for gasoline and Diesel 4 stroke engine

BIODEGRADABLE

100% Synthetic - Ester based

TYPE OF USE

All types of gasoline and Diesel engines. Turbocharged or not.

All 4 stroke engines : turbocharged or not, multivalve, carburettor or injection system, with or without catalytic converter.

Suitable for all types of fuel : leaded and unleaded gasoline, gasoil, LPG.

All types of use : racing, circuit, Road and off road rally, in town, road, motorway.

PERFORMANCES

Références SUBARU WRT

Exceeds standards : API SG / CD
CEC L-33-A-93 Biodegradability test.

Protects the environment. Contains biodegradable Esters from vegetable origin.
Very high lubricating power which decreases friction and wear.
Decreases fuel and oil consumption.

RECOMMENDATIONS

Oil change: according to manufacturers' requirements and according to your own use.
MOTUL 300V POWER can be mixed with synthetic or mineral lubricants.

PROPERTIES

Colour	Visual	Green
Viscosity grade	SAE J 300	5W-40
Density at 15°C (59°F)	ASTM D1298	0.893
Viscosity at 100°C (212°F)	ASTM D445	13.7 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	72.5 mm ² /s
Viscosity Index	ASTM D2270	196
Pour point	ASTM D97	-36°C / -33°F
Flash point	ASTM D92	222°C / 431°F
TBN	ASTM D 2896	11.5 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. - Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 - Site Web : www.motul.fr

3601

11/98