

MOTUL GEARBOX



Gearbox and rear axle lubricant

SAE 80W-90

Reinforced with molybdenum bisulphide

TYPE OF USE

Specially recommended for "noisy" gearboxes

All gearboxes and hypoid rear axles without limited slip system.

In gearboxes and rear axles with limited slip system, use MOTUL 90 PA, HYPO BM LS or HYPO SYNT LS.

In automatic gearboxes, use MOTUL DEXRON II D or MOTUL TRANSMISSION FLUID.

Meets SAE 80W to 90 manufacturers' requirements.

PERFORMANCE

STANDARDS API GL4 and GL5 / MIL-L-2105D

Very high lubricating power which decreases friction and wear.

The molybdenum bisulphide is a solid additive which gives very high resistance under heavy working conditions of use.

Thermal stability under high temperature.

Extreme pressure, Anti-wear, Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Multigrade mineral lubricant.

Viscosity grade	SAE J 306	80W-90
Density at 15°C (59°F)	ASTM D1298	0.904
Viscosity at 40°C (104°F)	ASTM D445	127 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	16.3 mm ² /s
Viscosity index	ASTM D2270	137
Flash point	ASTM D92	208°C / 406°F
Pour point	ASTM D97	-30°C / -22°F