

MOTUL KART GRAND PRIX 2T



Special 23 000 rpm GO Kart Lubricant

Premix Racing 2 stroke Engines

100% Synthetic Ester

TYPE OF USES

**Formula developed for racing GO KARTS
Suitable for all kinds of gasoline.**

Racing premix 2 stroke engines with very high RPM:
ROTAX, ATK, PARILLA, PCR, YAMAHA, Ital System, TM, ...

PERFORMANCES

STANDARDS: API TC - TSC 3
FMK approved

Very high lubricating power which decreases friction and wear.
Keeps engines always perfectly lubricated in extreme use conditions (23 000 rpm / high temperatures).

Prevents piston ring sticking.

Keeps engine clean contrary to 2 stroke standard racing oils.

RECOMMENDATIONS

Mixing ratio : 100 cc : 6%
 125 cc : 4%

Adjust according to your own use and to your tuner's recommendations.

PROPERTIES

100% synthetic ester lubricant.

Density at 15°C (59°F)	ASTM D1298	0.916
Viscosity at 100°C (212°F)	ASTM D445	16.4 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	127 mm ² /s
Viscosity index	ASTM D2270	139
Flash point	ASTM D92	250°C / 482°F
Pour point	ASTM D97	-33°C / -27°F

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE.

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 – Web Site : www.motul.com

03/00